

lix skinny Design: Klaus Nolting

lix skinny Design: Klaus Nolting



Technische Daten:

LED
Lithium-Ionen Akku . 1x 2600 mAh
Dim to Amber 2700K - 1800K

Betriebsdauer:
je nach Dimmstufe 5 Std. bis 48 Std.

Stromversorgung:
charging base mit 1,2 m USB-C-Kabel inklusive

Material:
• Farben BB + PW + JB + FS: Aluminiumguss lackiert + Polycarbonat matt
• Farben BA + CR + DC für den Innenbereich: Aluminiumguss beschichtet + Polycarbonat matt

Schutzart: IP44

Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse E

Lichtrichtung:



technical information:

LED
lithium-ion battery . 1x 2600 mAh
dim to amber 2700K - 1800K

battery operating time:
5 hrs. to 48 hrs., depending on the dimming level

power source:
charging base with 1,2 m USB-C-cable included







material:
• colours BB + PW + JB + FS: aluminium die-casting lacquered + polycarbonate matt
• colours BA + CR + DC for interior use: aluminium die-casting plated + polycarbonate matt

protection class: IP44

This product contains a light source of energy efficiency class E

light direction:



Farbe colour	Art.-Nr. item no.	Systemleistung system performance
 bright bronze	93932-BB	2 W/100 lm
pearl white	93932-PW	2 W/100 lm
 jet black	93932-JB	2 W/100 lm
 frozen silver	93932-FS	2 W/100 lm
 NEW brass	93932-BA	2 W/100 lm
 NEW chrome	93932-CR	2 W/100 lm
 NEW dark chrome	93932-DC	2 W/100 lm

Zubehör accessory	Artikel article	Art.-Nr. item no.
	USB-C-Ladegerät black USB-C-charger black	55921-BL
	solarbank	53410
	multi charging base	53420

+ verwandte Produkte related products . lix . lix mini . lix spike . lix spike solar

Größe in mm
size in mm