




**down.3 R** Design: IP44.DE



**Lichttechnik:**  
230V Power LED  
2700K  
L70/50.000 h

**Reflektor:** Flood + schwarz

dimmbar über Phasenabschrittdimmer  
optional mit integriertem DALI-2-Phasendimmer

**Installation:**  
1x Kabeleinführung; Anschlussklemme 3x 1,5 mm<sup>2</sup>

**Material:**  
Aluminiumguss pulverbeschichtet  
+ Sicherheitsglas klar

**Schutzart:** IP65

Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse F

**Lichtrichtung:**



**light technology:**  
230V Power LED  
2700K  
L70/50.000 h

**reflector:** flood + black

dimmbable via trailing edge dimmer  
with integrated DALI-2 phase dimmer as an option

**installation:**  
1x cable entry point; connection terminal 3x 1,5 mm<sup>2</sup>

**material:**  
aluminium die-casting powder-coated  
+ safety glass clear

**protection class:** IP65

This product contains a light source of energy efficiency class F

**light direction:**



**Farbe**  
colour



anthracite  
RAL 7016

**Art.-Nr.**  
item no.

92810-R-AN  
92810-R-AN-DR . DALI-2 ready

**Systemleistung**  
system performance

8 W/319 lm

pure white  
RAL 9016

92810-R-WH  
92810-R-WH-DR . DALI-2 ready

8 W/319 lm



deep black  
RAL 9005

92810-R-BL  
92810-R-BL-DR . DALI-2 ready

8 W/319 lm

+ verwandte Produkte related products . down.3 S

Größe in mm  
size in mm