




iem.2 Design: IP44.DE



Lichttechnik:
230V Power LED
2700K
L70/50.000 h

Reflektor: Flood + schwarz . Abstrahlwinkel 38°

dimmbar über Phasenabschrittdimmer
optional mit integriertem DALI-2-Phasendimmer

Installation:
2x Kabeleinführung; Anschlussklemme 3x 1,5 mm²

Material:
Aluminiumguss pulverbeschichtet
+ Sicherheitsglas klar

Schutzart: IP65

Dieses Produkt enthält eine Lichtquelle
der Energieeffizienzklasse F

Lichtrichtung:



light technology:
230V Power LED
2700K
L70/50.000 h

reflector: flood + black . beam angle 38°

dimmbable via trailing edge dimmer
with integrated DALI-2 phase dimmer as an option

installation:
2x cable entry point; connection terminal 3x 1,5 mm²



material:
aluminium die-casting powder-coated
+ safety glass clear

protection class: IP65

This product contains a light source of
energy efficiency class F

light direction:



Farbe colour	Art.-Nr. item no.	Systemleistung system performance
 anthracite RAL 7016	92282-AN 92282-AN-DR . DALI-2 ready	16 W/638 lm
 deep black RAL 9005	92282-BL 92282-BL-DR . DALI-2 ready	16 W/638 lm

+ verwandte Produkte related products . iem.2 down

Größe in mm
size in mm