




luci down Design: Klaus Nolting



Lichttechnik:
230V Power LED
2700K
L70/50.000 h

Reflektor: schwarz

dimmbar über Phasenabschrittdimmer
optional mit integriertem DALI-2-Phasendimmer

Installation:
2x Kabeleinführung; Anschlussklemme 3x 2,5 mm²

Material:
Aluminiumguss pulverbeschichtet + Glaslinse

Schutzart: IP65

Dieses Produkt enthält eine Lichtquelle
der Energieeffizienzklasse F

Lichtrichtung:



light technology:
230V Power LED
2700K
L70/50.000 h

reflector: black

dimmable via trailing edge dimmer
with integrated DALI-2 phase dimmer as an option

installation:
2x cable entry point; connection terminal 3x 2,5 mm²



material:
aluminium die-casting powder-coated + glass lens

protection class: IP65

This product contains a light source of
energy efficiency class F

light direction:



Farbe colour	Art.-Nr. item no.	Systemleistung system performance
 anthracite RAL 7016	93152-AN 93152-AN-DR . DALI-2 ready	6 W/360 lm
 deep black RAL 9005	93152-BL 93152-BL-DR . DALI-2 ready	6 W/360 lm

+ verwandte Produkte related products . luci . luci control

Größe in mm
size in mm